

# First-principles modelling of spin current in Co/NiCu spintronic terahertz emitters

Bezvikonnyi N.V.<sup>1,®</sup>, Kartsev A.I.<sup>1</sup>, Zhilyaev P.A.<sup>1</sup> and Buryakov A.M.<sup>1</sup>

<sup>1</sup> MIREA—Russian Technological University, Prospekt Vernadskogo 78, Moscow, 119454, None

® bezvikonnyj@mirea.ru

Spintronic terahertz emitters convert an ultrafast laser-driven spin current into a broadband THz transient via spin-orbit mediated spin-to-charge conversion. Here we model the spin-current generation in a Co/NiCu bilayer emitter by combining a thermodynamic diffusion formalism with the *ab initio* approach. Spin-polarized electronic configuration of a Co/NiCu supercell is obtained from density-functional theory calculations. The electronic structure for each spin channel is then propagated separately through the semiclassical Boltzmann transport equation with BoltzTraP2 [1] to extract spin-dependent electrical conductivity and Seebeck coefficients. Spin current and its dependence on temperature gradients and channel asymmetry were further calculated with the phenomenological framework proposed by Fognini *et al.* [2]. The resulting workflow provides a first-principles route to quantify interfacial influence on the spin-current in bilayered metallic THz emitters.

The study was supported by the Russian Science Foundation (grant No. 25-79-30019, <https://rscf.ru/project/25-79-30019/>).

- [1] Madsen G K H and Singh D J 2006 *Computer Physics Communications* **175** 67–71
- [2] Fognini A, Michlmayr T U, Vaterlaus A and Acremann Y 2017 *Journal of Physics: Condensed Matter* **29** 214002